

### **Model LB Waterer:**

Gallons: 18 **Opening:** 17 ½" Side Reach: 6 1/2" **Water Level:** 

2" - 3" from top of tub

#### **Drinking Height:**

20" Maximum or less

#### **Waterer Construction:**

• 1/2" Polyethylene Plastic

### **Tub & Float Construction:**

• 1/4" Polyethylene Plastic

#### **Base Tube Construction:**

- 3/16" Polyethylene Plastic
- 36" Tube no insulation
- · 61" & 87" Tubes partially insulated - 2" thick

#### Capacity:

- Dry Lot Beef: 200 Head
- · Range Cows: 100 Head

- 1. Lid (extended nonuse)
- 2. Model LB Waterer
- 3. Tub
- 4. 5 1/2" Polyethylene Float
- 5. 3/16" Cord & 3/8" Sleeve
- 6. 3" Polyurethane Insulation
- 7. 1/2" HD Valve
- 8. Valve Guard
- 9. 1/4" Floatless Valve
- 10. Support Rod

- 11. Quick Coupler & Adapter
- 12. Quick Coupler & Adapter
- 13. Ball Valve
- 14. Flexible Hose
- 15. Strainer & Flush Valve
- 16. Anchor Rod
- 17. 36" Base Tube
- 18. 1" Polyethylene Waterline not included

## 4 Valve Options

#### 025 - 1/4" Floatless Valve Pressure Feed Clean Water Only 1/4" Orifice 5/8" Ballcock Thread Avg: 40 PSI = 2.25 GPM Max:80 PSI = 3.25 GPM

#### 050 - 1/2" HD Valve

1/2" Orifice Inside: 3/4" NPT

Pressure Feed Outside: 1 3/8" Bolt Thd. Avg: 40 PSI = 10 GPM Max: 80 PSI = 18 GPM

# 375 - 3/8" HD Valve

Pressure Feed 3/8" Orifice Inside: 3/4" NPT Outside: 1 3/8" Bolt Thd. Avg: 40 PSI = 7 GPM Max: 120 PSI = 16 GPM


## 100 - 1" HD Valve

Gravity Feed - Pond 1" Orifice 1 1/4" NPT



Capacity may be reduced!

# Included:



B) Plumbing Tie Cord

C) Anchor Rods for LB (3 total)



## OPTIONAL

FF-1010 Filter Fabric 15' x 15' \$34.00

IC-1010

Ice Chipper 17" \$7.00

**Optional Base Tube Extensions:** 36" @ \$40.00 18" @ \$20.00,

Factory prices are F.O.B. at East Peru, lowa and subject to change without notice.